



## Key Features

<b>System Configurations</b>	<ul style="list-style-type: none"> <li>• <b>Applications:</b> Equine, Bovine, Ovine, Canine, Feline, etc.</li> <li>• 10" non-interlaced monitor</li> <li>• Two transducer connectors</li> <li>• Back lit control panel</li> <li>• 6-segment TGC</li> <li>• 256-frame cine loop</li> <li>• 1000 images storage</li> <li>• Tissue Harmonic Imaging</li> <li>• 4B images for OB AFI calculation</li> <li>• Annotation library for quick comment</li> <li>• Graph/text report function</li> <li>• DICOM storage SCU</li> <li>• User defined exam settings Intuitive soft key at the bottom of screen, clicking supported</li> <li>• Intuitive context dependent soft key</li> <li>• Patient information management system</li> <li>• USB image transfer and software upgrade</li> <li>• Laser jet printer driver installed, HP LaserJet P2015 (1007, 1008, 1320, 2035, 2055)</li> <li>• 65C15H micro-convex array transducer (5.0/6.0/7.5/8.0 MHz)</li> </ul>
<b>Options</b>	<ul style="list-style-type: none"> <li>• 75E40H rectal linear array transducer (6.0/7.5/8.5/10.0 MHz)</li> <li>• 35C60H convex array transducer (2.0/3.5/4.5/5.5 MHz)</li> <li>• 60C20H micro-convex array transducer (5.0/6.0/7.5/8.0 MHz)</li> <li>• 75L40H linear array transducer (6.0/7.5/8.5/10 MHz)</li> <li>• 65C13H endocavity transducer (5.0/6.5/8.0/9.0 MHz)</li> <li>• 65C15H micro-convex array transducer (5.0/6.0/7.5/8.0 MHz)</li> <li>• Needle-guided brackets</li> <li>• USB water-resistant footswitch</li> <li>• Mobile trolley</li> <li>• Wheeled transport case</li> <li>• B&amp;W Thermal printer, SONY UP-897MD</li> <li>• B&amp;W Thermal printer, MITSUBISHI P93W</li> </ul>