



## Key Features

<b>System Configurations</b>	<ul style="list-style-type: none"> <li>➤ <b>Imaging Features</b> <ul style="list-style-type: none"> <li>• Imaging Mode: B, B/B, B/M, 4B</li> <li>• Scanning Mode: electric convex/ Linear</li> <li>• Gray scale: 256</li> <li>• Scanning depth:                             <ul style="list-style-type: none"> <li>- Convex Probe: 240 mm</li> <li>- Linear Probe: 3-120 mm</li> <li>- Rectal linear array Probe: 100 mm</li> </ul> </li> <li>• TGC: 8 TGC adjustments</li> <li>• Cine loop: 512 frames</li> <li>• Gain: 0-100dB adjustable</li> </ul> </li> </ul>	<ul style="list-style-type: none"> <li>➤ <b>System Configuration</b> <ul style="list-style-type: none"> <li>• Platform: smartphones, tablet, laptop &amp; desktop.</li> <li>• Operating System (OS): Windows, iOS, Android</li> <li>• Maximum 512 frames cine loop storage, DICOM 3.0</li> <li>• Weight: 200 g (approx.)</li> <li>• Probe port: USB Type-A/USB type C</li> </ul> </li> </ul>
<b>Transducer</b>	<ul style="list-style-type: none"> <li>➤ <b>Convex Probe</b> <ul style="list-style-type: none"> <li>• Frequency Bandwidth: 2.5-4.5 MHz</li> <li>• Center Frequency: 3.5 MHz</li> </ul> </li> <li>➤ <b>Linear Probe</b> <ul style="list-style-type: none"> <li>• Frequency Bandwidth: 5-10 MHz</li> <li>• Center Frequency: 7.5MHz</li> </ul> </li> </ul>	<ul style="list-style-type: none"> <li>➤ <b>Rectal Linear Array Probe</b> <ul style="list-style-type: none"> <li>• Frequency Bandwidth: 4-8 MHz</li> <li>• Center Frequency: 6 MHz</li> </ul> </li> </ul>