



## Key Features

<b>Standard Configurations</b>	<ul style="list-style-type: none"> <li>• <b>Applications:</b> <ul style="list-style-type: none"> <li>– Equine, bovine, ovine, canine, feline and other organ sites diagnosis</li> </ul> </li> <li>• Windows XP system</li> <li>• Digital beamformer</li> <li>• Real-time point by point dynamic receive focusing technique</li> <li>• Dynamic Frequency Scanning technology</li> <li>• Real-time dynamic beam anodization</li> <li>• Real-time dynamic aperture imaging THI Tissue Harmonic Imaging Technology Optimization</li> <li>• 2D gray scale imaging</li> <li>• 3D reconstruction imaging</li> <li>• Display: 12.1 inches high-resolution LCD monitor</li> <li>• Multi-language system: Chinese, English, Spanish</li> </ul>
<b>Transducer</b>	<ul style="list-style-type: none"> <li>• Transducer Connector : One transducer port</li> <li>• Scanning Mode: Convex, Micro-convex, Linear, Endocavity</li> <li>• Rectal Linear Transducer: 75E40N (5/6.5/7.5/10MHz)</li> <li>• Convex Array Transducer: 35C60NB (2.0/3.0/3.5/4.0/5.0MHz, 70 degrees)</li> <li>• Micro-convex Array Transducer: 32C20NA (3.5/5.0/6.5/7.5MHz, 110 degrees)</li> <li>• Endocavity Array Transducer: 65C10NB (5/6.5/7.5 /10MHz, 150 degrees)</li> <li>• Linear Array Transducer: 75L40NA (5/6.5/7.5/10MHz)</li> </ul>